

Dial Reading Viscometer

The original viscometer that set the world standard

- Easy-to-select speeds
- Electronic drive means quiet, reliable operation
- Analog display
 - Shows % torque
 - Use Factor Finder to convert reading to centipoise
- Simple to use, easy setup
- 1-Year limited warranty
- Accuracy: $\pm 1.0\%$ of range
- Repeatability: $\pm 0.2\%$

What's Included

- Instrument
- 6 spindles (RV/HA/HB) or 4 spindles (LV)
- Spindle guard leg*
- Lab stand (Model G)
- Carrying case

*Not applicable to HA or HB torque models

Optional Accessories

- Viscosity standards
- RV/HA/HB-1 spindle
- Quick Action lab stand
- Temperature Bath
- Small Sample Adapter
- UL Adapter
- Thermosel
- Spiral Adapter
- DIN Adapter
- Quick Connect/Extension Links
- Vane Spindles



Easy Speed Adjustment and On/Off Control



| VISCOSITY RANGE cP(mPa·s) | | | SPEEDS | |
|------------------------------|-------|------|--------|----------------------|
| MODEL | Min. | Max. | RPM | Number of Increments |
| LVT | 1† | 2M | .3-60 | 8 |
| RVT | 100†† | 8M | .5-100 | 10 |
| HAT | 200†† | 16M | .5-100 | 10 |
| HBT | 800†† | 64M | .5-100 | 10 |

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles. †† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.
M = 1 million cP = Centipoise mPa·s = Millipascal·seconds